

# How to plug and unplug the power cord of the optical splitter



## Overview

Power Up: Connect the included 5V DC adapter to the splitter and plug it into an AC outlet. The J-Tech Digital 1x3 SPDIF Optical Audio Splitter allows you to distribute a single optical (TOSLINK) audio signal into three identical outputs simultaneously. This is ideal for sending audio from one source (Blu-ray player, game console, TV, streamer, etc. ) to multiple audio devices such as. Protect the power cord from being walked on or pinched particularly at plugs, convenience receptacles, and the point where they exit from the apparatus. Only use attachments/accessories specified by the manufacturer. Use only with the cart, stand, tripod, bracket, or table specified by the. INTRODUCTION This document provides instructions to install the Tellabs® OLT2 Optical Line Terminal (OLT2). For inquiries: [tutorialswithterry@gmail.com](mailto:tutorialswithterry@gmail.com). Learn more [How To Unplug Optical Audio Cable](#) | [How To Remove Optical Cable](#).

## How to plug and unplug the power cord of the optical splitter



Power Up: Connect the included 5V DC adapter to the splitter and plug it into an AC outlet. Connect the Optical Source: Using an optical (TOSLINK) cable, connect your source device's ...



Plug one end of the included USB Power Cable into the USB POWER port on the splitter, then plug the other end into a USB power source, such as a computer, wall charger, etc. (available separately).



Connect the end of the cable coming from the lighting console which will have a female 5-pin connector to the input connector of the DMX Splitter consisting of a male 5-pin connector.



INTRODUCTION This document provides instructions to install the Tellabs® OLT2 Optical Line Terminal (OLT2). The OLT2 is a self-contained and sealed unit, for mounting on a wall or in standard 19-in ...



The first step in removing an optical cable is to identify which cable you need to remove. This may seem obvious, but it's important to ensure that you are removing the correct cable to avoid ...



This device features a power outlet; install the device so that the outlet for the power cord is easily accessible. Unplug this apparatus during lightning storms or when unused for long ...



Power OFF all devices you plan to connect to this splitter. Connect your S/PDIF TOSLINK audio source to the splitter's Optical In using a TOSLINK Optical cable (cable not included).



Understanding how to properly place and use an optical splitter is essential for optimizing signal quality and ensuring seamless data transmission. Let's explore the best practices for ...



Setup Instructions: Connect an optical audio cable to the Digital Audio Output port of your source device and to the "In" port of the JTDSP0103 (In the connection diagram above, the Smart TV is the source ...



How To Unplug Optical Audio Cable | How To Remove Optical Cable. Quick Tutorial. For inquiries: [tutorialswithterry@gmail.com](mailto:tutorialswithterry@gmail.com) ...more



That's why I've made this short video. When pulling optical cable from TV, it feels a bit stuck. But, don't worry, just pull it out firmly and it'll come out.

## Contact Us

For more information, pricing, or custom network solutions, please contact us:

Website: <https://hashherbcafe.co.za>

Email: [hello@hashherbcafe.co.za](mailto:hello@hashherbcafe.co.za)

Phone: +27 63 814 7295

Address: 15 Galaxy Road, Linbro Business Park, Johannesburg, 2065, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

