

Laser diode 1310nm



Laser diode 13105w



The FP-1310-4I-LCx is an MOCVD grown InAlGaAs ridge laser diode with emission wave-length of 1310 nm and standard continuous light output of 5mW per facet. These lasers provide stable, single ...



Laser light emitted from any laser diode may be harmful to the human eye. Avoid looking directly into the laser diode's aperture. The use of optical lenses will increase eye hazard. Always do handle laser ...



BA-1310-CM-5W - Laser Diode from Innolume. Get product specifications, Download the Datasheet, Request a Quote and get pricing for BA-1310-CM-5W on GoPhotonics.



We offer fiber-coupled laser diodes for the most demanding scientific and industrial applications. Through the implementation of proprietary design, packaging, and fiber coupling technology, these ...




Choose your own fiber-coupled DFB, Fabry- Perrot or multimode laser diode + turn-key driver solution from 1270 to 1650 nm ociated with a CW or nanosecond pulsed turn-key driver. Multimode solutions ...



1310nm IR laser diodes and IR laser modules are available with both single-mode and multi-mode beam profiles. They have either free space or fiber coupled outputs.



All Brands on One Site, Compare Specifications and Get Pricing for 1310nm Laser Diodes, Unbiased SELECTION GUIDE, Research All of Your Choices and Select the Best



This device is an open - heat - sink diode laser; it can only be operated in a cleanroom environment or a dust - proof housing. Must control the operating temperature and relative humidity to avoid ...



The LD-1310-31B Fiber Coupled Laser Diode consists of Fabry-Perot lasers, having a fiber pigtail precisely attached for optimum coupling efficiency. This 1310 nm center wavelength version has a ...



The Optilab LD-1310P-DL is a high-power pulse laser diode has been designed as a light source for pulsed fiber lasers and CW applications. It is mostly utilized in combination with an external optical ...



Standard singlemode DFB or Fabry-Pérot laser diodes from 10 to 500mW are offered as stock items or associated with a low noise or ultra-low noise CW or nanosecond pulsed turn-key driver.



These fiber-coupled 1310 nm laser diodes are offered as stock items or associated with a low noise CW or Pulsed Laser Diode Driver. 4 models are single frequency versions (1310 nm DFB laser diode) up ...



Pigtailed Laser Diode Modules are available with VIS and NIR wavelengths ranging from 405 to 1550nm, with output powers ranging from 1 to 100mW. Their plug and play operation make these laser diodes ...

Contact Us

For more information, pricing, or custom network solutions, please contact us:

Website: <https://hashherbcafe.co.za>

Email: hello@hashherbcafe.co.za

Phone: +27 63 814 7295

Address: 15 Galaxy Road, Linbro Business Park, Johannesburg, 2065, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

