


Lebanese Retail SFP Optical Module PAM4



Lebanese Retail SFP Optical Module PAM4



200G/400G/800G optical module features up to 40km transmission distances using QSFP56/QSFP-DD footprints for data center interconnect applications - FiberMall



SFP Modules Items 1 - 20 of 72 SFP-1411 155Mbps Single-mode SFP Transceiver, 40km, 1310nm SFP-3711 1.25Gbps Single-mode SFP Transceiver, 120km, 1550nm



Supported by PAM4 modulation, it is a more cost-effective solution for 400G DCI with ultra-low power consumption. And it provides more flexibility and scalability since it has more lanes (8 or 4 lanes) ...



The 50g sfp56 module series is engineered to deliver 53.125Gbps via advanced PAM4 modulation. Manufactured in WolonFiber's state-of-the-art facilities, these transceivers bypass retail distributors ...



200G QSFP56 transceivers with PAM4 modulation for high-speed data center connectivity. SR4 and FR4 options supporting 100m to 2km reach. MSA compliant.



Siemon's 50G per lane PAM4 Ethernet or InfiniBand™ QSFP56 Active Optical Cable assemblies (AOCs) are designed to exceed industry standard performance offering a cost-effective, low latency, ...



The 400GBASE-SR4.2 module, MTP/MPO-12 connector, up to 150m over parallel OM5 multi-mode fiber. It is compliant to IEEE 802.3 protocol and 400GAUI ...



It builds on IEEE 802.3 and OIF CEI-112G-LINEAR-PAM4 specifications. It enables Ethernet-like links with 1, 2, 4, or 8 lanes for data centers, using low power, high port density, low cost, and low latency ...



Cisco SFP-50G-SL Short Link Modules are a replacement for traditional AOCs (Active Optical Cables). They are suitable for very short distances and offer a cost-effective way to connect ...



Samtec's FireFly™ Micro Flyover System™ embedded and rugged mid-board optical transceivers take data connection "off board" for up to 28 Gbps per lane with a path to 112 Gbps PAM4 via optical ...



200G Ethernet, Data centers, Data center Internal networks, Campus networks, Metropolitan networks, 5G wireless networks and other communication ...



MaxLinear provides a full range of DSPs and TIAs for applications ranging from 100G to 1.6T, supporting 100G and 200G per lane electrical and optical I/O on both the host and line side interfaces for AI ...



The 50GE PAM4 optical module uses the QSFP28 encapsulation mode, LC optical interfaces, and single-mode optical fibers. The transmission distance is 10/40 km, and the maximum power ...

Contact Us

For more information, pricing, or custom network solutions, please contact us:

Website: <https://hashherbcafe.co.za>

Email: hello@hashherbcafe.co.za

Phone: +27 63 814 7295

Address: 15 Galaxy Road, Linbro Business Park, Johannesburg, 2065, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

