

Manufacturer CFP8800G

Ordering information

NO.	1	2	3	4	5	6
Model	SFP12H1	SFP2H2	SFP4H4	SFP6H1	SFP12H2	SFP24H4
Product name	Patch Panel	Patch Panel	Patch Panel	Patch Panel	Patch Panel	Patch Panel
Illustration						
HU	1	2	4	1	2	4
Maximum number of cores	144	288	576	144	288	576
Product size (including modules and adapters)	482.6*371.1*44 mm	482.6*371.1*88.1 mm	482.6*371.1*177 mm	482.6*371.1*44 mm	482.6*371.1*88.1 mm	482.6*371.1*177 mm
Standard color code	RAL9005	RAL9005	RAL9005	RAL9005	RAL9005	RAL9005

Overview

Amphenol's CFP8 interconnect system has 124 contacts per port, with a 0.5mm contact pitch and 16 high speed channels. It is rated for 28Gb/s per channel with resonance dampening for improved signal integrity. The Cisco ® OSFP 800G transceiver modules provide 800 Gigabit Ethernet (GE), 2x 400GE, 4x 200GE, and 8x 100GE connectivity options, complying with the Octal Small Form Factor Pluggable (OSFP) MSA for pluggable transceivers. Note: Bosch completed its acquisition of FHP Manufacturing Company in 2007, and integrated FHP into Bosch's Thermotechnology division, BBT Thermotechnik GmbH. The date of production/manufacture or age of FHP (Florida Heat Pump) brand HVAC equipment can be determined from the serial number located. This Cisco® DS-SFP-FC8G-SW compatible SFP+ transceiver provides 8GBase-SW Fibre Channel throughput up to 150m over multi-mode fiber (MMF) using a wavelength of 850nm via an LC connector. This easy to install, hot. Using CAT. PoE Watchdog AI Function: Detection front-end PoE cameras and PD, Automatic detection, Automatic restart. Buying a refurbished product from Renewtech can provide significant savings of up to 80% off the original retail price of a brand-new.

Manufacturer CFP8800G



Certified and tested on Cisco OSFP 800G ports for superior performance, quality, and reliability. High-speed electrical and optical compliance with IEEE 802.3. Modules have the capability ...



How to determine the date of production/manufacture or age of FHP® (Florida Heat Pump) brand HVAC Systems. The industry average service design life for most forced air furnaces is ...



Supports 400G ~ 800Gb Ethernet systems. Ideal for 100 - 400 Gb Ethernet systems.




This Cisco® DS-SFP-FC8G-SW compatible SFP+ transceiver provides 8GBase-SW Fibre Channel throughput up to 150m over multi-mode fiber (MMF) using a wavelength of 850nm via an LC ...




Amphenol's 800G OSFP optical modules include 2xDR4(plus), 2xFR4(plus), 2xLR4, AOC, and AOC break-out series, which adopt LC or MPO optical ports and are compatible with IEEE802.3, OIF ...



Intelligent power distribution and secure power supply system. The port power is 60 watts, it is convenient for high-power device. Zero configuration feature power supply is automatically supplied ...



Designed to seamlessly integrate with existing infrastructure, this module supports a maximum data transfer rate of 8,000 Mbit/s, utilizing SFP+ interface for high-speed performance.



Heater voltage requirements: 120 VAC, 240 VAC optional. Do not energize until engine coolant has been installed. These units are available in both standard and high working pressures. Unit is ...

Contact Us

For more information, pricing, or custom network solutions, please contact us:

Website: <https://hashherbcafe.co.za>

Email: hello@hashherbcafe.co.za

Phone: +27 63 814 7295

Address: 15 Galaxy Road, Linbro Business Park, Johannesburg, 2065, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

